



HL TURN SIGNAL

LED DRIVE LIGHT INDICATOR / BLINKER

The HL Compact LED drive light can be complemented by TYRI's LED turn signal, designed to work perfectly alongside the HL Compact to create an aesthetically pleasing design.

This marker light is approved to ECE regulation 6, Categories 1 & 6.

SUGGESTED APPLICATIONS

The HL Turn Signal is highly adaptable and can be used across numerous applications worldwide, including:



TECHNICAL DATA

- Housing Material:** Cast Aluminium
- Mounting Options:** (2) M5 x 0.8 screws spaced 48 mm apart vertically. The aluminium heat sink has threaded holes
- Lens Material:** Amber coloured PC
- Temperature range:** -40 to +85 °C
- Connector:** DT04-2P / 350 mm harness
DT06-2S mating connector
- Operating Voltage:** 9-32 V
- Current Draw:** 0.42 A @ 12 V
- Weight:** 150 g / 0.33 lbs

- Overheating Protection
- Over-voltage Protection
- Polarity Protection

TEST STANDARDS

- Salt Spray ASTM B117 500 h
- Vibration 5-2000 Hz 3 Axis, 10 Grms
- Shock Tested 50 G 11 ms
- IP69K
- ECE Regulation 6, Categories 1 & 6
- EMC ECE Regulation 10

TYRI's testing standards can be found at: www.tyrilights.com

